

52" Non Woven Contract Wallcovering

PHYSICAL PROPERTIES

• **30% post-consumer recycled content**

- Content-natural fibers, man-made fibers

Weight 11.2 oz. PLY/347.3 G/PLM 7.5 oz. PSY/254.3 G/PSM

Width 52"/132 cm

Backing Osnaburg

Meets or exceeds Federal Specification CCC-W-408D physical characteristics for Type II Wallcovering

FIRE SAFETY

- Class "A" Fire rated - Tested in accordance with ASTM E-84 Tunnel Test
- Flame Spread 25/Smoke Developed 5

ENVIRONMENT & HEALTH

- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED MR 4.1 and MR 4.2 for recycled content
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials
- Can contribute to LEED MR 7 for certified wood

ANTI-MICROBIAL FEATURES

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at

www.VyconWallcovering.com Eco-Innovation for the Contract Market